



NUMINOS® CL DALI S

Indoor LED surface ceiling light white/black 2700K 60°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Like with the NUMINOS® CL DALI S indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 980 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?

TECHNICAL DATA

Item no.	1004416
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	10.42 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	72
Number of luminaires at LS C16A	122
Level of inrush current	52 A
Duration of inrush current	1 µs
Lumen	980 lm
Colour temperature	2700 Kelvin
Beam angle	60 °
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L80B50



Light Source

791819	
--------	---

Accessories

1006167	NUMINOS® S , white front ring
---------	-------------------------------

Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Height	16.2 cm
Diameter	6.5 cm
Net weight	0.56 kg
Gross weight	0.725 kg
BIG WHITE Page	104

