



3~ NUMINOS® DALI M

3 phase system light white/black 3000K 60°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the 3~ NUMINOS® DALI M 3-phase system light LED, which convinces with best workmanship and light quality. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1880 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

Item no.	1004472
Rotating or tilting	rotary Bar and tiltable
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20.1 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Number of luminaires at LS B16A	8
Number of luminaires at LS C16A	16
Level of inrush current	10 A
Duration of inrush current	30 µs
Lumen	1880 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L80B50



Light Source

791822	
--------	---

Accessories

1006168	NUMINOS® M , white front ring
---------	-------------------------------

Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Length	18.5 cm
Height	16.5 cm
Diameter	8.5 cm
Net weight	0.83 kg
Gross weight	1.13 kg
BIG WHITE Page	112

