


NUMINOS® PD DALI M

Indoor LED pendant light white/black 3000K 36°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Like with the NUMINOS® PD DALI M pendant light, which impresses with its high-quality workmanship and light. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The pendant light can convince with a power consumption of 20.1 watts, luminous flux of 1970 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

| | |
|---------------------------------|---------------------------|
| Item no. | 1004543 |
| Assembly | Surface |
| Assembly details | Ceiling,Ceiling with Acc. |
| Dimmable | Yes |
| Dimming technology | DALI |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 500 mA |
| Safety class | I |
| Wattage | 20.1 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 30 °C |
| Number of luminaires at LS B16A | 8 |
| Number of luminaires at LS C16A | 16 |
| Level of inrush current | 10 A |
| Duration of inrush current | 30 µs |
| Lumen | 1970 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 36 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 13 |
| LXXBXX data | L80B50 |

Light Source

| | |
|--------|---|
| 791822 |  |
|--------|---|

Accessories

| | |
|---------|-------------------------------|
| 1006168 | NUMINOS® M , white front ring |
|---------|-------------------------------|

| | |
|----------------|---------|
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 18.5 cm |
| Diameter | 8.5 cm |
| Pendant length | 250 cm |
| Net weight | 1.25 kg |
| Gross weight | 1.4 kg |
| BIG WHITE Page | 108 |