



3~ NUMINOS® DALI L

3 phase system light white/black 3000K 36°

The NUMINOS light system from SLV skilfully combines function, design and technology. With various downlights and spotlights, you provide a thousand lighting design options. Also with the 3~ NUMINOS® DALI L 3-phase system light LED, which convinces with best workmanship and light quality. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2340 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?

TECHNICAL DATA

Item no.	1004567
Rotating or tilting	rotary Bar and tiltable
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	28 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Number of luminaires at LS B16A	35
Number of luminaires at LS C16A	60
Level of inrush current	30 A
Duration of inrush current	2 µs
Lumen	2340 lm
Colour temperature	3000 Kelvin
Beam angle	36 °
Color	white
CRI	90
UGR ≤	13
LXXBXX data	L80B50



Light Source

791822	
--------	---

Accessories

1006169	NUMINOS® L , white front ring
---------	-------------------------------

Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Length	21.3 cm
Height	18 cm
Diameter	10 cm
Net weight	1.115 kg
Gross weight	1.45 kg
BIG WHITE Page	113