



### 3~ NUMINOS® DALI L

3 phase system light black/black 4000K 24°

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the 3~ NUMINOS® DALI L 3-phase system light LED, which impresses with its high-quality workmanship and light. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2675 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?

### TECHNICAL DATA

Item no.	1004570
Rotating or tilting	rotary Bar and tiltable
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	28 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Number of luminaires at LS B16A	35
Number of luminaires at LS C16A	60
Level of inrush current	30 A
Duration of inrush current	2 µs
Lumen	2675 lm
Colour temperature	4000 Kelvin
Beam angle	24 °
Color	black
CRI	90
UGR ≤	19
LXXBXX data	L80B50



## Light Source

791825	
--------	-----------------------------------------------------------------------------------

## Accessories

1006169	NUMINOS® L , white front ring
---------	-------------------------------

Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Length	21.3 cm
Height	18 cm
Diameter	10 cm
Net weight	1.115 kg
Gross weight	1.45 kg
BIG WHITE Page	113