




## NUMINOS® SPOT DALI L

Indoor LED recessed ceiling light black/black 4000K 60°

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® SPOT DALI L indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2715 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



## TECHNICAL DATA

|                                 |                         |
|---------------------------------|-------------------------|
| Item no.                        | 1004596                 |
| Rotating or tilting             | rotary Bar and tiltable |
| Assembly                        | Surface                 |
| Assembly details                | Ceiling                 |
| Dimmable                        | Yes                     |
| Dimming technology              | DALI                    |
| Primary nominal voltage         | 220-240V ~50/60Hz       |
| Secondary power / voltage       | 700 mA                  |
| Safety class                    | I                       |
| Wattage                         | 28 W                    |
| Minimum ambient temperature     | -20 °C                  |
| Maximum ambient temperature     | 30 °C                   |
| Number of luminaires at LS B16A | 35                      |
| Number of luminaires at LS C16A | 60                      |
| Level of inrush current         | 30 A                    |
| Duration of inrush current      | 2 µs                    |
| Lumen                           | 2715 lm                 |
| Colour temperature              | 4000 Kelvin             |
| Beam angle                      | 60 °                    |
| Color                           | black                   |
| CRI                             | 90                      |
| UGR ≤                           | 22                      |



## Light Source

|        |  |
|--------|--|
| 791825 |  |
|--------|--|

## Accessories

|         |                               |
|---------|-------------------------------|
| 1006169 | NUMINOS® L , white front ring |
|---------|-------------------------------|

|                    |                      |
|--------------------|----------------------|
| LXXBXX data        | L80B50               |
| Service life       | 50000 h              |
| Light distribution | rotational symmetric |
| Light outlet       | direct               |
| Risk Group         | 1                    |
| Length             | 21.3 cm              |
| Height             | 18 cm                |
| Diameter           | 10 cm                |
| Net weight         | 1.15 kg              |
| Gross weight       | 1.5 kg               |
| BIG WHITE Page     | 101                  |