




3~ SIGHT MOVE DALI

3 phase system light white 3000K

The modern SIGHT wall and ceiling light is made for surface mounting or busbar. The powerful luminous flux of 2700 lumens and the low glare the 3-phase system light LED an efficient basic lighting solution in offices or shops. The light made of aluminium and polymethylacrylate (PMMA) in the colour white and frosted cuts a professional figure everywhere. In addition, 3~ SIGHT MOVE DALI is also extremely sustainable with its LED lifespan of 30,000 hours. When will you test out the benefits of SLV's impressive indoor lights?



TECHNICAL DATA

Item no.	1004691
Number of different light outlets	1
Rotating or tilting	tiltable
IP Code	IP20
Assembly details	Track Ceiling, Track Wall
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	26 W
Minimum ambient temperature	-30 °C
Maximum ambient temperature	40 °C
Rated standby power	0.29 W
Number of luminaires at LS B16A	43
Number of luminaires at LS C16A	63
Stroboscopic effect (SVM)	0
Lumen	2700 lm
Colour temperature	3000 Kelvin
Beam angle	75 °
Color	white
CRI	90



Light Source

916350	
--------	---

UGR \leq	25
LXXBXX data	L90B20
Service life	50000 h
Light outlet	direct
Risk Group	1
Length	45 cm
Width	5.6 cm
Height	10.5 cm
Net weight	1.248 kg
Gross weight	1.511 kg
BIG WHITE Page	533

