




## PANEL TRACK square 150x300mm

1-phase spot, black, 18W 3000K

Modern and space-saving at the same time, PANEL provides efficient basic lighting. With 1,800 lumens and 3,000 Kelvin, the 1-phase system light LED produces a pleasant, homogeneous and glare-free light. Made of polycarbonate (PC) and steel, it is also extremely sustainable with an LED lifespan of 50,000 hours. Experience light with SLV – your reliable partner for all kinds of indoor lights for 40 years.



## TECHNICAL DATA

Item no.	1004933
Number of different light outlets	1
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Impact resistance	0.2 Joule
Assembly details	Track Ceiling, Track Wall
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	450 mA
Safety class	II
Wattage	18 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	15 A
Duration of inrush current	20 µs
Stroboscopic effect (SVM)	0.01
Lumen	1800 lm
Colour temperature	3000 Kelvin
Color	black
CRI	90
UGR ≤	27.5
LXXBXX data	L70B50
Service life	50000 h



## Light Source

916390 

Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Length	30 cm
Width	15 cm
Height	10.9 cm
Net weight	0.535 kg
Gross weight	0.692 kg
BIG WHITE Page	507