




## PANEL TRACK round 200mm

1-phase spot, black, 18W 3000K

With the modern and space-saving PANEL, you provide efficient basic lighting. A pleasant, homogeneous and glare-free light is produced by the 1-phase system light LED with 1,800 lumen and 3,000 Kelvin. The light is made of polycarbonate (PC) and steel and has a long LED lifespan of 50,000 hours. Experience light with SLV – your reliable partner for all kinds of indoor lights for 40 years.



## TECHNICAL DATA

Item no.	1004935
Number of different light outlets	1
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Impact resistance	0.2 Joule
Assembly details	Track Ceiling, Track Wall
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	450 mA
Safety class	II
Wattage	18 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	15 A
Duration of inrush current	20 µs
Stroboscopic effect (SVM)	0.01
Lumen	1800 lm
Colour temperature	3000 Kelvin
Color	black
CRI	90
LXXBXX data	L70B50
Service life	50000 h
Light distribution	rotational symmetric



## Light Source

916407	
--------	---

Light outlet	direct
Risk Group	1
Length	23.1 cm
Width	20 cm
Height	11.05 cm
Net weight	0.446 kg
Gross weight	0.602 kg
BIG WHITE Page	507