



## WORKLIGHT DALI

white pendant light, 57W 4000K 80°



As a consistent further development of our WORKLIGHT series, this WORKLIGHT is an office pendant light for screen-based workstations, equipped with state-of-the-art technology and highly efficient, high-output LEDs and of course  $UGR \leq 19$ . The light can be controlled via DALI. The WORKLIGHT is ready for direct connection to a 230V mains power supply thanks to its pre-installed driver and supply cable. This light contains integrated LED light bulbs.

## TECHNICAL DATA

Item no.	1005396
Number of different light outlets	2
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	200-240V ~50/60Hz
Secondary power / voltage	1550 mA
Safety class	I
Wattage	57 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Level of inrush current	5.1 A
Duration of inrush current	148 $\mu$ s
Temperature at glass (light emission)	40 °C
Stroboscopic effect (SVM)	0.01
Lumen	5000 lm
Colour temperature	4000 Kelvin
Beam angle	80 °



## Light Source

916322	
916564	

Color	white
CRI	80
UGR $\leq$	19
LXXBXX data	L80B10
Service life	50000 h
Risk Group	0
Length	120 cm
Width	26 cm
Height	3 cm
Pendant length	250 cm
Net weight	5.8 kg
Gross weight	6.206 kg
BIG WHITE Page	288

