



## MILANDOS 6

**black recessed ceiling light, 3000K 45°**



Minimalist, innovative and compact in design, the MILANDOS recessed ceiling light creates high-quality lighting. The long LED lifespan of 60,000 hours and the high colour reproduction index of over 90 are also convincing across the board. With a UGR of 16, it produces glare-free light. The simple design of the recessed ceiling light made of aluminium and polycarbonate (PC) blends seamlessly into any room. The spotlight is also quick and easy to install. Experience MILANDOS in action and convince yourself of a successful lighting experience.

## TECHNICAL DATA

Item no.	1005416
IP Code	IP 20
Impact resistance class	IK 02
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	700 mA
Safety class	III
Wattage	12 W
Ambient temperature	30 °C
Lumen	780 lm
Colour temperature	3000 Kelvin
Beam angle	45 °
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L80B50
Service life	60000 h
Risk Group	1
Length	19.6 cm
Width	5.6 cm
Height	4.3 cm
Net weight	0.3 kg



## Light Source

1078215	
998089	

## Accessories

1002423	LED driver MEDO 300 , dimmable DALI/1-10V
1006202	LED Driver , 20W 700mA

Gross weight	0.321 kg
Shape of cut-out	square
Installation length	19 cm
Installation width	4.9 cm
Installation depth	7 cm
BIG WHITE Page	217

