



## NUMINOS® XS

**black recessed ceiling light, 4000K 20°**

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. The diverse downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® XS recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

## TECHNICAL DATA

|                             |               |
|-----------------------------|---------------|
| Item no.                    | 1005535       |
| IP Code                     | IP 20 / IP 44 |
| Impact resistance class     | IK 02         |
| Impact resistance           | 0.2 Joule     |
| Assembly                    | Recessed      |
| Assembly details            | Ceiling       |
| Secondary power / voltage   | 200 mA        |
| Safety class                | III           |
| Wattage                     | 7 W           |
| Minimum ambient temperature | -20 °C        |
| Maximum ambient temperature | 40 °C         |
| Lumen                       | 720 lm        |
| Colour temperature          | 4000 Kelvin   |
| Beam angle                  | 20 °          |
| Color                       | black         |
| CRI                         | 90            |
| UGR ≤                       | 16            |
| LXXBXX data                 | L80B50        |
| Service life                | 50000 h       |
| Risk Group                  | 2             |
| Height                      | 4.5 cm        |
| Diameter                    | 6.5 cm        |

## Light Source

|        |   |
|--------|---|
| 798305 |  |
|--------|---|

## Accessories

|         |  |
|---------|--|
| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector  |
| 1005614 | NUMINOS® XS , frosted diffuser   |
| 1006454 | RF module Casambi for LED bridge driver , single colour                                    |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour                                |
| 1005612 | NUMINOS® XS , diffuser   |
| 1005610 | LED Driver , 200mA 10-W, Quick Connector   |
| 1005615 | NUMINOS® XS , black diffuser   |
| 1005611 | LED Driver , 200mA 13,5W DALI dimmable, Quick Connector                                    |
| 1005613 | NUMINOS® XS , transparent diffuser   |
| 1006457 | LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI |

|                       |          |
|-----------------------|----------|
| Net weight            | 0.115 kg |
| Gross weight          | 0.135 kg |
| Shape of cut-out      | round    |
| Installation depth    | 11 cm    |
| Installation diameter | 5.5 cm   |
| BIG WHITE Page        | 84       |