



NUMINOS® MOVE XS

white / black recessed ceiling light, 4000K 20°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. This also includes NUMINOS® MOVE XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. This means that simple installation is a mere formality. When do you choose NUMINOS® from SLV?

TECHNICAL DATA

| | |
|-----------------------------|-------------------------|
| Item no. | 1005598 |
| Rotating or tilting | rotary bar and tiltable |
| IP Code | IP 20 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 200 mA |
| Safety class | III |
| Wattage | 7 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 720 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 20 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 16 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Risk Group | 2 |
| Height | 5.5 cm |

Light Source

| | |
|--------|---|
| 798305 |  |
|--------|---|

Accessories

| | |
|---------|--|
| 1006136 | Numinos® XS Reducing ring , round 160/70mm white |
| 1006135 | Numinos® XS Reducing ring , round 160/70mm black |
| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector |
| 1005614 | NUMINOS® XS , frosted diffuser |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1005612 | NUMINOS® XS , diffuser |
| 1005610 | LED Driver , 200mA 10-W, Quick Connector |
| 1005615 | NUMINOS® XS , black diffuser |
| 1006137 | Numinos® XS Reducing ring , square 160/70mm black |
| 1005611 | LED Driver , 200mA 13,5W DALI dimmable, Quick Connector |
| 1006138 | Numinos® XS Reducing ring , square 160/70mm white |
| 1005613 | NUMINOS® XS , transparent diffuser |
| 1006457 | LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI |

| | |
|-----------------------|----------|
| Diameter | 8 cm |
| Net weight | 0.135 kg |
| Gross weight | 0.165 kg |
| Shape of cut-out | round |
| Installation depth | 8 cm |
| Installation diameter | 6.8 cm |
| BIG WHITE Page | 86 |