



NUMINOS® XL PHASE

black ceiling mounted light, 36W 4000K 24°

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Like with the NUMINOS® XL PHASE indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. The spotlight is perfect for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 36 watts, luminous flux of 3800 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?

TECHNICAL DATA

| Item no. | 1005699 |
|-----------------------------------|-------------------|
| Number of different light outlets | 1 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 900 mA |
| Safety class | I |
| Wattage | 36 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Level of inrush current | 4.64 A |
| Duration of inrush current | 224 µs |
| Stroboscopic effect (SVM) | 0.02 |
| Lumen | 3800 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 24 ° |
| Color | black |
| CRI | 90 |
| UGR≤ | 19 |
| LXXBXX data | L80B50 |
| | |







Light Source

| 791850 | A E |
|-------------|--------------------------------|
| Accessories | |
| 1006170 | NUMINOS® XL , white front ring |

| Service life | 50000 h |
|----------------|---------|
| Risk Group | 1 |
| Height | 25.8 cm |
| Diameter | 12 cm |
| Net weight | 1.63 kg |
| Gross weight | 2 kg |
| BIG WHITE Page | 105 |



