




## NUMINOS® XL PHASE

black pendant light, 36W 2700K 60°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® XL PHASE, which impresses as a pendant light with the best workmanship and lighting quality. The spotlight is perfect for targeted accent lighting or even illumination of larger areas. The pendant light can convince with a power consumption of 36 watts, luminous flux of 2980 lumens, colour temperature of 2700 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



## TECHNICAL DATA

Item no.	1005707
Number of different light outlets	1
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	36 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	4.64 A
Duration of inrush current	224 µs
Stroboscopic effect (SVM)	0.02
Lumen	2980 lm
Colour temperature	2700 Kelvin
Beam angle	60 °
Color	black
CRI	90
UGR ≤	25
LXXBXX data	L80B50



## Light Source

791857 

Service life	50000 h
Risk Group	1
Height	25.8 cm
Diameter	12 cm
Pendant length	250 cm
Net weight	2 kg
Gross weight	2.25 kg
BIG WHITE Page	105

