




NUMINOS® XL PHASE

white / black pendant light, 36W 4000K 36°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® XL PHASE pendant light, which impresses with its high-quality workmanship and light. The spotlight is perfect for targeted accent lighting or even illumination of larger areas. The pendant light can convince with a power consumption of 36 watts, luminous flux of 3760 lumens, colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.	1005721
Number of different light outlets	1
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	36 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	4.64 A
Duration of inrush current	224 µs
Stroboscopic effect (SVM)	0.02
Lumen	3760 lm
Colour temperature	4000 Kelvin
Beam angle	36 °
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L80B50



Light Source

791850 

Service life	50000 h
Risk Group	1
Height	25.8 cm
Diameter	12 cm
Pendant length	250 cm
Net weight	2 kg
Gross weight	2.25 kg
BIG WHITE Page	105