



NUMINOS® XL PHASE

black 3-phase spot, 36W 2700K 36°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® XL PHASE 3-phase system light LED, which convinces with best workmanship and light quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 36 watts, luminous flux of 3250 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?

TECHNICAL DATA

Item no.	1005724
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	36 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	4.64 A
Duration of inrush current	224 µs
Stroboscopic effect (SVM)	0.02
Lumen	3250 lm
Colour temperature	2700 Kelvin
Beam angle	36 °
Color	black
CRI	90
UGR ≤	19
LXXBXX data	L80B50



Light Source

791857 

Service life	50000 h
Risk Group	1
Length	25.8 cm
Height	20 cm
Diameter	12 cm
Net weight	1.63 kg
Gross weight	2 kg
BIG WHITE Page	113

