



NUMINOS® XL PHASE

black 3-phase spot, 36W 3000K 36°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® XL PHASE 3-phase system light LED, which convinces with best workmanship and light quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 36 watts, luminous flux of 3490 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

TECHNICAL DATA

Item no.	1005730
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	36 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	4.64 A
Duration of inrush current	224 µs
Stroboscopic effect (SVM)	0.02
Lumen	3490 lm
Colour temperature	3000 Kelvin
Beam angle	36 °
Color	black
CRI	90
UGR ≤	19
LXXBXX data	L80B50



Light Source

791823 

Service life	50000 h
Risk Group	1
Length	25.8 cm
Height	20 cm
Diameter	12 cm
Net weight	1.63 kg
Gross weight	2 kg
BIG WHITE Page	113