



NUMINOS® XL PHASE

white / black 3-phase spot, 36W 3000K 24°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. The different downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® XL PHASE 3-phase system light LED, which convinces with best workmanship and light quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 36 watts, luminous flux of 3530 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?

TECHNICAL DATA

| | |
|-----------------------------------|-------------------------|
| Item no. | 1005732 |
| Number of different light outlets | 1 |
| Rotating or tilting | rotary bar and tiltable |
| Assembly details | Track Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 900 mA |
| Safety class | I |
| Wattage | 36 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Level of inrush current | 4.64 A |
| Duration of inrush current | 224 µs |
| Stroboscopic effect (SVM) | 0.02 |
| Lumen | 3530 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 24 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 19 |
| LXXBXX data | L80B50 |



Light Source

791823 

| | |
|----------------|---------|
| Service life | 50000 h |
| Risk Group | 1 |
| Length | 25.8 cm |
| Height | 20 cm |
| Diameter | 12 cm |
| Net weight | 1.63 kg |
| Gross weight | 2 kg |
| BIG WHITE Page | 113 |