



## NUMINOS® XL PHASE

white / black 3-phase spot, 36W 4000K 60°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® XL PHASE 3-phase system light LED, which convinces with best workmanship and light quality. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 36 watts, luminous flux of 3460 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

## TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1005740                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| Assembly details                  | Track Ceiling           |
| Dimmable                          | Yes                     |
| Dimming technology                | trailing edge           |
| Primary nominal voltage           | 220-240V ~50/60Hz       |
| Secondary power / voltage         | 900 mA                  |
| Safety class                      | I                       |
| Wattage                           | 36 W                    |
| Minimum ambient temperature       | -20 °C                  |
| Maximum ambient temperature       | 35 °C                   |
| Level of inrush current           | 4.64 A                  |
| Duration of inrush current        | 224 µs                  |
| Stroboscopic effect (SVM)         | 0.02                    |
| Lumen                             | 3460 lm                 |
| Colour temperature                | 4000 Kelvin             |
| Beam angle                        | 60 °                    |
| Color                             | white                   |
| CRI                               | 90                      |
| UGR ≤                             | 25                      |
| LXXBXX data                       | L80B50                  |



## Light Source

791850 

|                |         |
|----------------|---------|
| Service life   | 50000 h |
| Risk Group     | 1       |
| Length         | 25.8 cm |
| Height         | 20 cm   |
| Diameter       | 12 cm   |
| Net weight     | 1.63 kg |
| Gross weight   | 2 kg    |
| BIG WHITE Page | 113     |