




NUMINOS® SPOT DALI XL

white / black ceiling mounted light, 36W 3000K 24 $\!^{\circ}$

The NUMINOS light system from SLV perfectly combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Also with the NUMINOS® SPOT DALI XL indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 36 watts, luminous flux of 3530 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.	1005750
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	900 mA
Safety class	1
Wattage	36 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	18
Number of luminaires at LS C16A	18
Level of inrush current	15 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0
Lumen	3530 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	white





Light Source

791823	A E
Accessories	
1006170	NUMINOS® XL , white front ring

CRI	90
UGR≤	19
LXXBXX data	L80B50
Service life	50000 h
Length	25.8 cm
Height	20 cm
Diameter	12 cm
Net weight	1.5 kg
Gross weight	2 kg
BIG WHITE Page	101

