



NUMINOS® DALIXL

black ceiling mounted light, 36W 3000K 24°

The NUMINOS light system from SLV skilfully combines function, design and technology. With different downlights and spotlights, you provide a thousand lighting design possibilities. Like with the NUMINOS® DALI XL indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 36 watts, luminous flux of 3530 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?

TECHNICAL DATA

umber of different light outlets ssembly ssembly details immable Yes	
ssembly details immable Yes	
immable Yes	ng
imming technology DAL	I
rimary nominal voltage 220	-240V ~50/60Hz
econdary power / voltage 900	mA
afety class	
attage 36 V	V
inimum ambient temperature -20	°C
aximum ambient temperature 35°	C
umber of luminaires at LS B16A 18	
umber of luminaires at LS C16A 18	
evel of inrush current 15 A	\ \
uration of inrush current 100	μs
troboscopic effect (SVM)	
umen 353	O lm
olour temperature 300) Kelvin
eam angle 24 °	
olor blac	k
RI 90	







Light Source

791823	A E
Accessories	
1006170	NUMINOS® XL , white front ring

UGR≤	19
LXXBXX data	L80B50
Service life	50000 h
Height	25.8 cm
Diameter	12 cm
Net weight	1.5 kg
Gross weight	1.85 kg
BIG WHITE Page	105



