



NUMINOS® DALIXL

black ceiling mounted light, 36W 4000K 24°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With a variety of downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINO-S® DALI XL indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The recessed ceiling light convinces with a power consumption of 36 watts, luminous flux of 3800 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?

TECHNICAL DATA

| Item no. | 1005771 |
|-----------------------------------|-------------------|
| Number of different light outlets | 1 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 900 mA |
| Safety class | I |
| Wattage | 36 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Number of luminaires at LS B16A | 18 |
| Number of luminaires at LS C16A | 18 |
| Level of inrush current | 15 A |
| Duration of inrush current | 100 µs |
| Stroboscopic effect (SVM) | 0 |
| Lumen | 3800 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 24 ° |
| Color | black |
| CRI | 90 |
| | 1 |







Light Source

| 791850 | A E |
|-------------|--------------------------------|
| Accessories | |
| 1006170 | NUMINOS® XL , white front ring |

| UGR≤ | 19 |
|----------------|---------|
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Height | 25.8 cm |
| Diameter | 12 cm |
| Net weight | 1.5 kg |
| Gross weight | 1.85 kg |
| BIG WHITE Page | 105 |

