




NUMINOS® DALI XL

white / black pendant light, 36W 2700K 24°

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. This also includes NUMINOS® DALI XL, which impresses as a pendant light with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The pendant light has a power consumption of 36 watts, a luminous flux of 3290 lumens, a colour temperature of 2700 Kelvin and a good colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

| | |
|-----------------------------------|-------------------|
| Item no. | 1005780 |
| Number of different light outlets | 1 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 900 mA |
| Safety class | I |
| Wattage | 36 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Number of luminaires at LS B16A | 18 |
| Number of luminaires at LS C16A | 18 |
| Level of inrush current | 15 A |
| Duration of inrush current | 100 µs |
| Stroboscopic effect (SVM) | 0 |
| Lumen | 3290 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 24 ° |
| Color | white |
| CRI | 90 |

Light Source

| | |
|--------|---|
| 791857 |  |
|--------|---|

Accessories

| | |
|---------|--------------------------------|
| 1006170 | NUMINOS® XL , white front ring |
|---------|--------------------------------|

| | |
|----------------|---------|
| UGR \leq | 19 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Height | 25.8 cm |
| Diameter | 12 cm |
| Pendant length | 250 cm |
| Net weight | 2 kg |
| Gross weight | 2.3 kg |
| BIG WHITE Page | 109 |