




NUMINOS® DALIXL

white / black pendant light, 36W 3000K 24 $^{\circ}$

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. The various downlights and spotlights make a thousand lighting design options possible. This also includes NUMINO-S® DALI XL, which impresses as a pendant light with the best workmanship and lighting quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The pendant light can convince with a power consumption of 36 watts, luminous flux of 3530 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

Item no.	1005786
Number of different light outlets	1
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	36 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	18
Number of luminaires at LS C16A	18
Level of inrush current	15 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0
Lumen	3530 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	white
CRI	90





Light Source

791823	A E
Accessories	
1006170	NUMINOS® XL , white front ring

UGR≤	19
LXXBXX data	L80B50
Service life	50000 h
Height	25.8 cm
Diameter	12 cm
Pendant length	250 cm
Net weight	2 kg
Gross weight	2.3 kg
BIG WHITE Page	109

