




NUMINOS® DALIXL

black pendant light, 36W 4000K 60°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With various downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINO-S® DALI XL pendant light, which impresses with its high-quality workmanship and light. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The pendant light has a power consumption of 36 watts, a luminous flux of 3460 lumens, a colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV - modular diversity awaits you.



TECHNICAL DATA

| Item no. | 1005791 |
|-----------------------------------|-------------------|
| Number of different light outlets | 1 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 900 mA |
| Safety class | I |
| Wattage | 36 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Number of luminaires at LS B16A | 18 |
| Number of luminaires at LS C16A | 18 |
| Level of inrush current | 15 A |
| Duration of inrush current | 100 μs |
| Stroboscopic effect (SVM) | 0 |
| Lumen | 3460 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 60 ° |
| Color | black |
| CRI | 90 |
| | |







Light Source

| 791850 | A E |
|-------------|--------------------------------|
| Accessories | |
| 1006170 | NUMINOS® XL , white front ring |

| UGR≤ | 25 |
|----------------|---------|
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Height | 25.8 cm |
| Diameter | 12 cm |
| Pendant length | 250 cm |
| Net weight | 2 kg |
| Gross weight | 2.3 kg |
| BIG WHITE Page | 109 |

