




## **NUMINOS® DALIXL**

white / black pendant light, 36W 4000K  $36^{\circ}$ 

The NUMINOS light system from SLV skilfully combines function, design and technology. With different downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® DALI XL, which impresses as a pendant light with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The pendant light has a power consumption of 36 watts, a luminous flux of 3760 lumens, a colour temperature of 4000 Kelvin and a good colour reproduction index of over 90. This means that simple installation is a mere formality. When to choose NUMINOS from SLV - modular diversity awaits you.



## **TECHNICAL DATA**

Item no.	1005793
Number of different light outlets	1
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	36 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	18
Number of luminaires at LS C16A	18
Level of inrush current	15 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0
Lumen	3760 lm
Colour temperature	4000 Kelvin
Beam angle	36 °
Color	white
CRI	90
	<del>'</del>





## Light Source

791850	A E
Accessories	
1006170	NUMINOS® XL , white front ring

UGR≤	19
LXXBXX data	L80B50
Service life	50000 h
Height	25.8 cm
Diameter	12 cm
Pendant length	250 cm
Net weight	2 kg
Gross weight	2.3 kg
BIG WHITE Page	109

