



NUMINOS® DALI XL

white / black 3-phase spot, 36W 3000K 60°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® DALI XL 3-phase system light LED, which convinces with best workmanship and light quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 36 watts, luminous flux of 3210 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS® from SLV?

TECHNICAL DATA

Item no.	1005806
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	36 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	18
Number of luminaires at LS C16A	18
Level of inrush current	15 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0
Lumen	3210 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	white
CRI	90



Light Source

791823	
--------	---

Accessories

1006170	NUMINOS® XL , white front ring
---------	--------------------------------

UGR ≤	25
LXXBXX data	L80B50
Service life	50000 h
Risk Group	1
Length	25.8 cm
Height	20 cm
Diameter	12 cm
Net weight	1.55 kg
Gross weight	1.95 kg
BIG WHITE Page	113

