



NUMINOS® GIMBLE XS

black / white recessed ceiling light, 2700K 55°

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. With different downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® GIMBLE XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. This means that simple installation is a mere formality. When to choose NUMINOS from SLV - modular diversity awaits you.

TECHNICAL DATA

Item no.	1005820
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	7 W
Lumen	670 lm
Colour temperature	2700 Kelvin
Beam angle	55 °
Color	black
CRI	90
UGR≤	25
LXXBXX data	L80B50
Service life	50000 h
Risk Group	1
Height	5.7 cm
Diameter	8 cm
Net weight	0.13 kg
Gross weight	0.15 kg
Shape of cut-out	round







Light Source

798300	A F	
Accessories		
1006136	Numinos® XS Reducing ring , round 160/70mm white	
1006135	Numinos® XS Reducing ring , round 160/70mm black	
1005609	LED Driver , 200mA 10W PHASE, Quick Connector	
1005614	NUMINOS® XS , frosted diffuser	
1006454	RF module Casambi for LED bridge driver , single colour	
1006199	RF module Zigbee for DALI LED bridge driver , single colour	
1005612	NUMINOS® XS , diffuser	
1005610	LED Driver , 200mA 10- W, Quick Connector	
1005615	NUMINOS® XS , black diffuser	
1006137	Numinos® XS Reducing ring , square 160/70mm black	
1005611	LED Driver , 200mA 13,5W DALI dimmable, Quick Connector	
1006138	Numinos® XS Reducing ring , square 160/70mm white	
1005613	NUMINOS® XS , transparent diffuser	
1006457	LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI	

Installation depth	8 cm
Installation diameter	6.8 cm
BIG WHITE Page	88