



NUMINOS® GIMBLE S

black / white recessed ceiling light, 3000K 40°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With various downlights and spotlights, you provide a thousand lighting design options. This also includes NUMINOS® GIMBLE S, which impresses as a recessed ceiling light with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

| | |
|-----------------------------------|-------------------------|
| Item no. | 1005889 |
| Number of different light outlets | 1 |
| Rotating or tilting | rotary bar and tiltable |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 250 mA |
| Safety class | III |
| Wattage | 8.6 W |
| Lumen | 730 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 40 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 19 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 7 cm |
| Diameter | 10 cm |
| Net weight | 0.2 kg |
| Gross weight | 0.24 kg |
| Shape of cut-out | round |

Light Source

| | |
|--------|-----------------------------------------------------------------------------------|
| 791815 |  |
|--------|-----------------------------------------------------------------------------------|

Accessories

| | |
|---------|--------------------------------------------------------------------------------------------|
| 1006458 | LED bridge driver , 12W, 250mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004789 | NUMINOS® S , diffuser Wabe |
| 1004067 | LED driver , 15W 250mA DALI |
| 1004788 | NUMINOS® S , diffuser Frosted |
| 1004787 | NUMINOS® S , diffuser Prisma |
| 1004786 | NUMINOS® S , diffuser Ellipse |
| 1006139 | Numinos® S Reducing ring , round 160/100mm black |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1004058 | LED driver , 6.5-10W 250mA |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1006140 | Numinos® S Reducing ring , round 160/100mm white |
| 1006142 | Numinos® S Reducing ring , square 160/100mm white |
| 1004055 | LED driver , 6.5-10W 250mA PHASE |
| 1006141 | Numinos® S Reducing ring , square 160/100mm black |

| | |
|-----------------------|------|
| Installation depth | 7 cm |
| Installation diameter | 9 cm |
| BIG WHITE Page | 88 |