



## NUMINOS® GIMBLE L

**black / chrome recessed ceiling light, 2700K 240°**

The NUMINOS light system from SLV skilfully combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® GIMBLE L recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When will you choose SLV's modular variety?

## TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1005977                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 700 mA                  |
| Safety class                      | III                     |
| Wattage                           | 25.4 W                  |
| Lumen                             | 2150 lm                 |
| Colour temperature                | 2700 Kelvin             |
| Beam angle                        | 20 °                    |
| Color                             | black                   |
| CRI                               | 90                      |
| UGR ≤                             | 22                      |
| LXXBXX data                       | L80B50                  |
| Service life                      | 50000 h                 |
| Risk Group                        | 1                       |
| Height                            | 11.5 cm                 |
| Diameter                          | 16 cm                   |
| Net weight                        | 0.6 kg                  |
| Gross weight                      | 0.75 kg                 |
| Shape of cut-out                  | round                   |

## Light Source

|        |   |
|--------|---|
| 791800 |  |
|--------|---|

## Accessories

|         |  |
|---------|--|
| 1006148 | Numinos® L Reducing ring , round 240/150mm white   |
| 1006149 | Numinos® L Reducing ring , square 240/150mm black  |
| 1004062 | LED driver , 21-29.5W 500/600/700mA for Numinos Downlight Serie                            |
| 1004795 | NUMINOS® L , diffuser Prisma   |
| 1004796 | NUMINOS® L , diffuser Frosted  |
| 1006460 | LED bridge driver , 42W, 700mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004794 | NUMINOS® L , diffuser Ellipse  |
| 1006150 | Numinos® L Reducing ring , square 240/150mm white  |
| 1006454 | RF module Casambi for LED bridge driver , single colour                                    |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour                                |
| 1006147 | Numinos® L Reducing ring , round 240/150mm black   |
| 1004070 | LED driver , 40W 700mA DALI  |
| 1004797 | NUMINOS® L , diffuser Wabe   |
| 1004065 | LED driver , 30W 700mA   |

|                       |         |
|-----------------------|---------|
| Installation depth    | 11.5 cm |
| Installation diameter | 14.5 cm |
| BIG WHITE Page        | 89      |

