



NUMINOS® ZOOM M PHASE

black 3-phase spot, 20W 4000K 15-60°


NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® ZOOM M PHASE 3-phase system light LED, which convinces with best workmanship and light quality. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?

TECHNICAL DATA

| | |
|-----------------------------------|-------------------------|
| Item no. | 1006112 |
| Number of different light outlets | 1 |
| Rotating or tilting | rotary bar and tiltable |
| Assembly details | Track Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 500 mA |
| Safety class | I |
| Wattage | 20 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Stroboscopic effect (SVM) | 0.03 |
| Lumen | 780-1900 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 15 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 25 |
| LXXBXX data | L70B50 |
| Service life | 40000 h |
| Risk Group | 1 |



Light Source

| | |
|--------|---|
| 791825 |  |
|--------|---|

| | |
|----------------|----------|
| Length | 19 cm |
| Height | 16.5 cm |
| Diameter | 8.5 cm |
| Net weight | 0.984 kg |
| Gross weight | 1.296 kg |
| BIG WHITE Page | 115 |

