



VANO WING SP DALI

Wall-mounted light grey 49W 3140lm 3000K CRI80
120° DALI

Ideal for surface, display and advertising sign lighting: the aluminium and glass VANO WING SP DALI spotlight is an excellent choice for outdoor areas. And thanks to DALI it can be controlled and dimmed via digital control signals. Surface illumination can be achieved even with minimal spacing thanks to the wide beam angle of 120 degrees and the asymmetric reflector. The warm white light (3000 K) offers excellent intensity thanks to a luminous flux of 3140 lumen. Thanks to its IP65 protection class rating, this spotlight is ideally protected against moisture penetration. And the integrated ballast makes it quick and easy to connect to the mains.

TECHNICAL DATA

Item no.	1006270
Number of different light outlets	1
Rotating or tilting	tiltable
IP Code	IP 65
Impact resistance class	IK 06
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling,Ground,Wall
Dimmable	Yes
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	1050 mA
Safety class	I
Wattage	49 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Network rated standby power	0.22 W
Level of inrush current	24 A
Duration of inrush current	220 µs
Stroboscopic effect (SVM)	0.01
Lumen	3140 lm
Colour temperature	3000 Kelvin

Light Source

1319287



Beam angle	120 °
Color	grey
CRI	80
LXXBXX data	L70B50
Service life	50000 h
Light distribution	symmetric
Light outlet	direct
Risk Group	0
Width	119.5 cm
Height	6.5 cm
Depth	20.5 cm
Net weight	6 kg
Gross weight	6.42 kg
BIG WHITE Page	719