



ENOLA OCULUS CL

**Ceiling-mounted light anthracite 11W 1000/1100lm
3000/4000K CRI90 100°**

Minimalist design with a sharply delineated light: the cylindrical ENOLA OCULUS CL uses special lens technology, which makes it the perfect accent lighting source. At the same time, this aluminium and glass ceiling light can withstand dirt and jets of water from all angles thanks to its IP65 protection class rating. The light colour (3000/4000K) in this 1000 / 1100 lumen outdoor light can be adjusted using the CCT switch before installation. The ENOLA OCULUS CL also has impressive characteristics such as a CRI of over 90 and an installation panel (supplied with the light) that enables a quick connection to a 220 volt supply.

TECHNICAL DATA

| | |
|-----------------------------|----------------------------|
| Item no. | 1006327 |
| IP Code | IP 65 |
| Impact resistance class | IK 03 |
| Impact resistance | 0.35 Joule |
| Assembly | Surface |
| Assembly details | Ceiling, Ceiling with Acc. |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 500 mA |
| Safety class | I |
| Wattage | 11 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 30 °C |
| Level of inrush current | 4.7 A |
| Duration of inrush current | 30 µs |
| Stroboscopic effect (SVM) | 0.01 |
| Lumen | 1000/1100 lm |
| Colour temperature | 3000/4000 Kelvin |
| Beam angle | 100 ° |
| Color | anthracite |
| CRI | 90 |
| LXXBXX data | L70B50 |
| Service life | 30000 h |



Light Source

| | |
|--------|---|
| 916566 |  |
|--------|---|

Accessories

| | |
|---------|--|
| 1003479 | Spacer set , for the ENOLA SQUARE OUT and ROUND OUT ceiling lights in anthracite |
|---------|--|

| | |
|----------------|----------|
| Risk Group | 1 |
| Height | 12 cm |
| Diameter | 10 cm |
| Net weight | 0.758 kg |
| Gross weight | 0.951 kg |
| BIG WHITE Page | 792 |

