



## **RUSTY® PATHLIGHT40**

LED outdoor floor stand, rust coloured, IP55, 3000K

The direct radiating floor stands of the RUSTY series convince by their exceptional rust look. This is achieved by a special chemical treatment of the FeCSi steel used. This makes the luminaire a unique piece and an absolutely special feature wherever they are installed. With protection class IP55, it is suitable for outdoor use. As an option an earth spike as well as a connection box for safe electrical connection to the round luminaire upright, are available. Equipped with a powerful LED, the luminaire connects directly to a 230V mains voltage supply.

## **TECHNICAL DATA**

Item no.	1006346
Number of different light outlets	1
IP Code	IP 55
Impact resistance class	IK 06
Impact resistance	1 Joule
Assembly	Surface
Assembly details	Ground
Primary nominal voltage	220-240V ~50/60Hz
Safety class	I
Wattage	8.8 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Stroboscopic effect (SVM)	0.05
Lumen	470 lm
Colour temperature	3000 Kelvin
Beam angle	90 °
Color	rust
CRI	80
LXXBXX data	L70B50
Service life	25000 h
Length	15 cm
Width	25 cm







## **Light Source**

954785	A E
Accessories	
228730	CONNECTION BOX , 3-pin, IP68
229422	Earth spike , galvanised steel, 50 cm

Height	40 cm
Net weight	12.705 kg
Gross weight	13.966 kg