




## CONCRETO L

**WL wall-mounted light grey, 12W, 570lm, 3000K**

A high-quality feature made from fashionable concrete: the rectangular CONCRETO L wall-mounted light adds a fresh touch to outdoor areas. With a colour temperature of 3000 Kelvin, the integrated LED bulb emits an inviting, warm white light with a particularly sustainable lifespan of 50,000 hours. The grey concrete lamp has an IP65 protection class rating that offers protection in any weather.



## TECHNICAL DATA

Item no.	1006405
IP Code	IP 65
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Assembly	Surface
Assembly details	Wall
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	II
Wattage	12 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Operating efficiency (LOR)	0,33
Number of luminaires at LS B16A	61
Number of luminaires at LS C16A	61
Level of inrush current	9 A
Duration of inrush current	150 µs
Temperature at glass (light emission)	40 °C
Stroboscopic effect (SVM)	0.05
Lumen	470 lm
Colour temperature	3000 Kelvin
Color	grey



## Light Source

1319290	
---------	--

CRI	80
LXXBXX data	L80B50
Service life	50000 h
Risk Group	0
Width	37.5 cm
Height	25 cm
Depth	8 cm
Net weight	5.3 kg
Gross weight	5.671 kg
BIG WHITE Page	717

