




IN-LINE 44 48V TRACK

opal, DALI, spot, black 14W, 1140lm, 2700K, CRI90, 95°

Plain linear luminaires for a particularly elegant look: the IN-LINE spotlight is concealed within a 48V TRACK system, allowing only the best feature to surface: high-quality light with a 35° beam angle in various lumen and natural colour reproduction (CRI>90). The DALI-compatible IN-LINE linear luminaires are also quick and easy to install via a track adapter.




TECHNICAL DATA

Item no.	1006621
Number of different light outlets	1
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly details	Track,Track Ceiling,Track Wall
Dimmable	Yes
Dimming technology	DALI 2
Primary nominal voltage	48V
Secondary power / voltage	350 mA
Safety class	III
Wattage	14 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Network rated standby power	0.5 W
Stroboscopic effect (SVM)	0.4
Lumen	1140 lm
Colour temperature	2700 Kelvin
Beam angle	95 °
Color	black
CRI	90
UGR ≤	28



Light Source



LXXBXX data	L80B50
Service life	50000 h
Risk Group	1
Length	43.5 cm
Width	2.2 cm
Height	2.5 cm
Net weight	0.279 kg
Gross weight	0.299 kg
BIG WHITE Page	475

