




## IN-LINE 46 48V TRACK

Move DALI, Darklight Reflector, spot, black / black, 14W, 1180lm, 2700K, CRI90, 35°

Plain linear luminaires for a particularly elegant look: the IN-LINE spotlight is concealed within a 48V TRACK system, allowing only the best feature to surface: high-quality light with a 35° beam angle in various lumen, adjustable lighting colour via a CCT switch (2700K/3000K/4000K) and natural colour reproduction (CRI>90). As a result, the DARKLIGHT REFLECTOR creates an atmosphere that particularly showcases restaurants, bars and hotels in a new light. The DALI-compatible and pivoting IN-LINE linear luminaires are also quick and easy to install via a track adapter.



## TECHNICAL DATA

Item no.	1006645
Number of different light outlets	1
Rotating or tilting	tiltable
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly details	Track,Track Ceiling,Track Wall
Dimmable	Yes
Dimming technology	DALI 2
Primary nominal voltage	48V
Secondary power / voltage	350 mA
Safety class	III
Wattage	14 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Rated standby power	0.5 W
Stroboscopic effect (SVM)	0.4
Lumen	1180 lm
Colour temperature	2700 Kelvin
Beam angle	35 °
Color	black
CRI	90



## Light Source


---

UGR $\leq$	16
LXXBXX data	L80B50
Service life	50000 h
Risk Group	1
Length	45.5 cm
Width	2.2 cm
Height	5.8 cm
Net weight	0.531 kg
Gross weight	0.568 kg
BIG WHITE Page	477

