



NUMINOS® S 48V TRACK

DALI, spot, black / black, 16W, 1060lm, 3000K, CRI90, 20°

High-quality minimalism across the board: the compact NUMINOS® spotlights provide elegant yet effective illumination with a 48V track system. They also perfectly complement the most discerning room designs with their clear, cylindrical shape. The brightness, light colour (2700-K/3000K/4000K) and half-peak divergence (20°/ 40°/55°) of these DALI-compatible spotlights can be adjusted as desired. The aluminium housing is available in black, white and chrome. A CRI value over 90 ensures natural colour reproduction. The adjustable and pivoting spotlights are quick and easy to install thanks to the track adapter.



TECHNICAL DATA

Item no.	1006723
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly details	Track,Track Ceiling,Track Wall
Dimmable	Yes
Dimming technology	DALI 2
Primary nominal voltage	48V
Secondary power / voltage	350 mA
Safety class	III
Wattage	16 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Network rated standby power	0.5 W
Lumen	1060 lm
Colour temperature	3000 Kelvin
Beam angle	20 °
Color	black
CRI	90
UGR ≤	19

Light Source

791815	
--------	---

Accessories

1004789	NUMINOS® S , diffuser Wabe
1004788	NUMINOS® S , diffuser Frosted
1004787	NUMINOS® S , diffuser Prisma
1004786	NUMINOS® S , diffuser Ellipse

LXXBXX data	L80B50
Service life	50000 h
Risk Group	1
Height	9 cm
Diameter	6 cm
Net weight	0.326 kg
Gross weight	0.349 kg
BIG WHITE Page	469