




NUMINOS® S 48V TRACK

DALI, spot, black / white, 16W, 1120lm, 3000K, CRI90, 55°

High-quality minimalism across the board: the compact NUMINOS® spotlights provide elegant yet effective illumination with a 48V track system. They also perfectly complement the most discerning room designs with their clear, cylindrical shape. The brightness, light colour (2700-K/3000K/4000K) and half-peak divergence (20°/ 40°/55°) of these DALI-compatible spotlights can be adjusted as desired. The aluminium housing is available in black, white and chrome. A CRI value over 90 ensures natural colour reproduction. The adjustable and pivoting spotlights are quick and easy to install thanks to the track adapter.



TECHNICAL DATA

| | |
|-----------------------------------|--------------------------------|
| Item no. | 1006730 |
| Number of different light outlets | 1 |
| Rotating or tilting | rotary bar and tiltable |
| IP Code | IP 20 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly details | Track,Track Ceiling,Track Wall |
| Dimmable | Yes |
| Dimming technology | DALI 2 |
| Primary nominal voltage | 48V |
| Secondary power / voltage | 350 mA |
| Safety class | III |
| Wattage | 16 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Network rated standby power | 0.5 W |
| Lumen | 1120 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 55 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 22 |

Light Source

| | |
|--------|---|
| 791815 |  |
|--------|---|

Accessories

| | |
|---------|----------------------------------|
| 1004789 | NUMINOS® S , diffuser Wabe |
| 1004788 | NUMINOS® S , diffuser Frosted |
| 1004787 | NUMINOS® S , diffuser Prisma |
| 1004786 | NUMINOS® S , diffuser Ellipse |

| | |
|----------------|----------|
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 9 cm |
| Diameter | 6 cm |
| Net weight | 0.326 kg |
| Gross weight | 0.349 kg |
| BIG WHITE Page | 469 |