


NUMINOS® XS 48V TRACK

DALI, pendant light, black / white, 8.7W, 650lm, 2700K, CRI90, 40°

High-quality minimalism across the board: the compact NUMINOS® pendant lights provide elegant yet effective illumination with a 48V track system. They also perfectly complement the most discerning room designs with their clear, cylindrical shape. The brightness, light colour (2700-K/3000K/4000K) and half-peak divergence (20°/ 40°/55°) of these DALI-compatible spotlights can be adjusted as desired. The aluminium housing is available in black, white and chrome. A CRI value over 90 ensures natural colour reproduction. The pendant lights are quick and easy to install thanks to the track adapter.



TECHNICAL DATA

Item no.	1006763
Number of different light outlets	1
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly details	Track, Track Ceiling
Dimmable	Yes
Dimming technology	DALI 2
Primary nominal voltage	48V
Secondary power / voltage	200 mA
Safety class	III
Wattage	8.7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Network rated standby power	0.5 W
Lumen	650 lm
Colour temperature	2700 Kelvin
Beam angle	40 °
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B50

Light Source

798300	
--------	---

Accessories

1005614	NUMINOS® XS , frosted diffuser
1005612	NUMINOS® XS , diffuser
1005615	NUMINOS® XS , black diffuser
1005613	NUMINOS® XS , transparent diffuser

Service life	50000 h
Risk Group	1
Height	8 cm
Diameter	5 cm
Pendant length	150 cm
Net weight	0.211 kg
Gross weight	0.226 kg
BIG WHITE Page	471