




NUMINOS® PROJECTOR XS

recessed ceiling light, 3000 K, 20°, cylindrical, white / white

Outstanding LED technology, harmonious design and a diverse range of applications: the NUMINOS® PROJECTOR recessed ceiling light effectively illuminates elegant living rooms, shops, restaurants, hotels and museums. The spot emits a high-quality light with different colour temperatures (2700K/3000K/4000K) and half-peak divergence (20°/40°/55°) that is suitable for various projects. The beam can be tilted and rotated to light up a large area. The housing is available in black or white, the decorative reflector in black, white or chrome.



TECHNICAL DATA

| | |
|-----------------------------------|-------------------------|
| Item no. | 1006895 |
| Number of different light outlets | 1 |
| Rotating or tilting | rotary bar and tiltable |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 200 mA |
| Safety class | III |
| Wattage | 7 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 730 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 20 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 16 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Risk Group | 1 |
| Length | 8 cm |
| Diameter | 4.9 cm |
| Net weight | 0.24 kg |

Light Source

| | |
|--------|-----------------------------------------------------------------------------------|
| 798303 |  |
|--------|-----------------------------------------------------------------------------------|

Accessories

| | |
|---------|--------------------------------------------------------------------------------------------|
| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector |
| 1005614 | NUMINOS® XS , frosted diffuser |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1005612 | NUMINOS® XS , diffuser |
| 1005610 | LED Driver , 200mA 10-W, Quick Connector |
| 1005615 | NUMINOS® XS , black diffuser |
| 1005611 | LED Driver , 200mA 13,5W DALI dimmable, Quick Connector |
| 1005613 | NUMINOS® XS , transparent diffuser |
| 1006457 | LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI |

| | |
|-----------------------|----------|
| Gross weight | 0.257 kg |
| Shape of cut-out | round |
| Installation depth | 10 cm |
| Installation diameter | 6.8 cm |
| BIG WHITE Page | 92 |