



## NUMINOS® PROJECTOR S

recessed ceiling light, 2700 K, 20°, cylindrical, white / black

Outstanding LED technology, harmonious design and a diverse range of applications: the NUMINOS® PROJECTOR recessed ceiling light effectively illuminates elegant living rooms, shops, restaurants, hotels and museums. The spot emits a high-quality light with different colour temperatures (2700K/3000K/4000K) and half-peak divergence (20°/40°/55°) that is suitable for various projects. The beam can be tilted and rotated to light up a large area. The housing is available in black or white, the decorative reflector in black, white or chrome.



### TECHNICAL DATA

Item no.	1006930
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	250 mA
Safety class	III
Wattage	8.6 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	670 lm
Colour temperature	2700 Kelvin
Beam angle	20 °
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L80B50
Service life	50000 h
Risk Group	1
Length	12.5 cm
Diameter	6 cm
Net weight	0.55 kg

## Light Source

791819	
--------	---

## Accessories

1006458	LED bridge driver , 12W, 250mA for NUMINOS®, including radio interface for RF module, DALI
1004789	NUMINOS® S , diffuser Wabe
1004067	LED driver , 15W 250mA DALI
1004788	NUMINOS® S , diffuser Frosted
1004787	NUMINOS® S , diffuser Prisma
1004786	NUMINOS® S , diffuser Ellipse
1006454	RF module Casambi for LED bridge driver , single colour
1004058	LED driver , 6.5-10W 250mA
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1004055	LED driver , 6.5-10W 250mA PHASE

Gross weight	0.589 kg
Shape of cut-out	round
Installation depth	15 cm
Installation diameter	8.8 cm
BIG WHITE Page	92