



NUMINOS® PROJECTOR S

recessed ceiling light, 3000 K, 55°, cylindrical, white / chrome

Outstanding LED technology, harmonious design and a diverse range of applications: the NUMINOS® PROJECTOR recessed ceiling light effectively illuminates elegant living rooms, shops, restaurants, hotels and museums. The spot emits a high-quality light with different colour temperatures (2700K/3000K/4000K) and half-peak divergence (20°/40°/55°) that is suitable for various projects. The beam can be tilted and rotated to light up a large area. The housing is available in black or white, the decorative reflector in black, white or chrome.



TECHNICAL DATA

| | |
|-----------------------------------|-------------------------|
| Item no. | 1006956 |
| Number of different light outlets | 1 |
| Rotating or tilting | rotary bar and tiltable |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 250 mA |
| Safety class | III |
| Wattage | 8.6 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 700 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 55 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Risk Group | 1 |
| Length | 12.5 cm |
| Diameter | 6 cm |
| Net weight | 0.55 kg |

Light Source

| | |
|--------|---|
| 791815 |  |
|--------|---|

Accessories

| | |
|---------|--|
| 1006458 | LED bridge driver , 12W, 250mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004789 | NUMINOS® S , diffuser Wabe |
| 1004067 | LED driver , 15W 250mA DALI |
| 1004788 | NUMINOS® S , diffuser Frosted |
| 1004787 | NUMINOS® S , diffuser Prisma |
| 1004786 | NUMINOS® S , diffuser Ellipse |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1004058 | LED driver , 6.5-10W 250mA |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1004055 | LED driver , 6.5-10W 250mA PHASE |

| | |
|-----------------------|----------|
| Gross weight | 0.589 kg |
| Shape of cut-out | round |
| Installation depth | 15 cm |
| Installation diameter | 8.8 cm |
| BIG WHITE Page | 92 |