



## NUMINOS® PROJECTOR L

recessed ceiling light, 3000 K, 55°, cylindrical, black / white

Outstanding LED technology, harmonious design and a diverse range of applications: the NUMINOS® PROJECTOR recessed ceiling light effectively illuminates elegant living rooms, shops, restaurants, hotels and museums. The spot emits a high-quality light with different colour temperatures (2700K/3000K/4000K) and half-peak divergence (20°/40°/55°) that is suitable for various projects. The beam can be tilted and rotated to light up a large area. The housing is available in black or white, the decorative reflector in black, white or chrome.



### TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1007054                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 700 mA                  |
| Safety class                      | III                     |
| Wattage                           | 25.4 W                  |
| Minimum ambient temperature       | -20 °C                  |
| Maximum ambient temperature       | 40 °C                   |
| Lumen                             | 2300 lm                 |
| Colour temperature                | 3000 Kelvin             |
| Beam angle                        | 55 °                    |
| Color                             | black                   |
| CRI                               | 90                      |
| UGR ≤                             | 22                      |
| LXXBXX data                       | L80B50                  |
| Service life                      | 50000 h                 |
| Risk Group                        | 1                       |
| Length                            | 13 cm                   |
| Diameter                          | 10 cm                   |
| Net weight                        | 0.95 kg                 |

## Light Source

|        |   |
|--------|---|
| 791822 |  |
|--------|---|

## Accessories

|         |   |
|---------|---|
| 1004062 | LED driver , 21-29.5W<br>500/600/700mA for Numi-<br>nos Downlight Serie                             |
| 1004795 | NUMINOS® L , diffuser<br>Prisma   |
| 1004796 | NUMINOS® L , diffuser<br>Frosted  |
| 1006460 | LED bridge driver , 42W,<br>700mA for NUMINOS®,<br>including radio interface<br>for RF module, DALI |
| 1004794 | NUMINOS® L , diffuser<br>Ellipse  |
| 1006454 | RF module Casambi for<br>LED bridge driver , single<br>colour                                       |
| 1006199 | RF module Zigbee for<br>DALI LED bridge driver ,<br>single colour                                   |
| 1004070 | LED driver , 40W 700mA<br>DALI  |
| 1004797 | NUMINOS® L , diffuser<br>Wabe   |
| 1004065 | LED driver , 30W 700mA  |

|                       |          |
|-----------------------|----------|
| Gross weight          | 1.017 kg |
| Shape of cut-out      | round    |
| Installation depth    | 15 cm    |
| Installation diameter | 13 cm    |
| BIG WHITE Page        | 93       |