




QUADRULO

wall-mounted light, 3000K, anthracite/brown

Aluminium LED wall light from the QUADRULO range with a clear illuminated area. Thanks to its high IP rating, this light is suitable for outdoor use and comes with or without a motion sensor. The electrical connection can be connected directly to the 230V mains power supply.



TECHNICAL DATA

Item no.	1007207
IP Code	IP 55
Impact resistance class	IK 04
Assembly	Surface
Assembly details	Wall
Number of through-wires	20
Primary nominal voltage	100-277V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	7.4 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	103
Number of luminaires at LS C16A	103
Level of inrush current	5 A
Duration of inrush current	25 µs
Stroboscopic effect (SVM)	0.01
Lumen	280 lm
Colour temperature	3000 Kelvin
Color	anthracite
CRI	80
LXXBXX data	L70B50



Light Source

916332	
--------	---

Service life	30000 h
Risk Group	0
Width	12.5 cm
Height	25 cm
Depth	13.2 cm
Net weight	0.97 kg
Gross weight	1.038 kg
BIG WHITE Page	744