




M-POL S Polehead 360°

low-glare, lamp head, anthracite, 10W, 750lm, 2700K, CRI80, DALI

M-POL means the SLV outdoor family whose members bear individual lamp heads. The M-POL S Polehead also leads the way here: the DALI-dimmable, low-glare and 2700K warm-white beam of light illuminates the path, which avoids light pollution and contributes to a dark sky. Thanks to its IP65 rating, the lamp heads are wind and weather-proof and the IK10 protection class even means they are protected against heavy impact. Simply perfect for illuminating outdoor commercial areas in high quality.



TECHNICAL DATA

Item no.	1007233
IP Code	IP 65
Impact resistance class	IK 10
Impact resistance	20 Joule
Assembly details	Ground with Acc.
Dimmable	Yes
Dimming technology	DALI
Number of through-wires	20
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Wattage	10 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Operating efficiency (LOR)	0,54
Rated standby power	0.5 W
Number of luminaires at LS B16A	80
Number of luminaires at LS C16A	100
Level of inrush current	15 A
Duration of inrush current	100 µs
Lumen	750 lm
Colour temperature	2700 Kelvin
Color	anthracite

Light Source



Accessories

1006381	M-POL 90 Pole , Bollard, anthracite, 83.4cm
1006453	Connection box , 5-pin, IP68, black, DALI
1006379	M-POL 30 Pole , Bollard, anthracite, 23.4cm
1006380	M-POL 60 Pole , Bollard, anthracite, 53.4cm
1006382	M-POL ground anchor , stainless steel
228725	CONNECTION BOX , 5-pin, IP68

CRI	80
LXXBXX data	L80B50
Service life	50000 h
Risk Group	1
Height	16.4 cm
Diameter	12.09 cm
Net weight	1.05 kg
Gross weight	1.124 kg
BIG WHITE Page	614

