




## I-RING

wall-mounted light, 9.2W, 3000K, anthracite

Indirect lighting in an organic ring shape summed up: the new I-RING wall light creates flexible and warm-white (3000K) accented lighting in upmarket outdoor areas thanks to its pivoting and rotatable lamp head. It also prevents light pollution as far as possible. The anthracite-coloured outdoor light is optimally protected thanks to its IP65 rating and features an exceptionally long lifespan of 50,000 hours. A well-rounded lighting experience.




## TECHNICAL DATA

Item no.	1007236
Rotating or tilting	Rotary bar and tiltable
IP Code	IP 65
Impact resistance class	IK 05
Assembly	Surface
Assembly details	Wall
Number of through-wires	20
Primary nominal voltage	100-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	9.2 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	45 °C
Operating efficiency (LOR)	0,54
Number of luminaires at LS B16A	50
Number of luminaires at LS C16A	80
Level of inrush current	12 A
Duration of inrush current	300 µs
Stroboscopic effect (SVM)	0.03
Lumen	670 lm
Colour temperature	3000 Kelvin
Color	anthracite



## Light Source

1807467	
---------	---

CRI	80
LXXBXX data	L70B50
Service life	50000 h
Risk Group	0
Depth	8.2 cm
Diameter	24 cm
Net weight	0.95 kg
Gross weight	1.017 kg
BIG WHITE Page	714

