




DASAR 2.0 XL square cover 24° 3000K incl. DALI driver in stainless steel

The accessible DASAR 2.0 recessed floor light is impressive along its entire length: the linear housing with its round or square cover made of glass and stainless steel is equally stable and of high quality. With its narrow beam angle and warm white light color temperature of 3000 Kelvin, it ensures cosy, uniform outdoor lighting. The CRI value above 80 ensures the most natural color reproduction possible. DASAR is a truly compelling light experience that can be controlled digitally via DALI.;



TECHNICAL DATA

| | |
|---------------------------------------|-------------------|
| Item no. | 1007242 |
| IP Code | IP 65 / IP 67 |
| Impact resistance class | IK 10 |
| Impact resistance | 20 Joule |
| Assembly | Recessed |
| Assembly details | Ground with Acc. |
| Dimmable | Yes |
| Dimming technology | DALI, Touch |
| Number of through-wires | 30 |
| Mechanical loading | 2 t |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 700 mA |
| Safety class | I |
| Wattage | 27 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 45 °C |
| Number of luminaires at LS B16A | 30 |
| Number of luminaires at LS C16A | 30 |
| Level of inrush current | 30 A |
| Duration of inrush current | 25 μ s |
| Temperature at glass (light emission) | 60 °C |
| Stroboscopic effect (SVM) | 0.06 |

Light Source

| | |
|---------|---|
| 1807464 |  |
|---------|---|

Accessories

| | |
|---------|-----------------------------------|
| 1007246 | Mounting housing for DASAR 2.0 XL |
| 1007239 | Reflector for DASAR 2.0 36° |
| 1007238 | Reflector for DASAR 2.0 15° |
| 1007240 | Reflector for DASAR 2.0 60° |

| | |
|-----------------------|-----------------|
| Lumen | 2790 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 24 ° |
| Color | stainless steel |
| CRI | 80 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Risk Group | 1 |
| Length | 27 cm |
| Width | 27 cm |
| Depth | 21 cm |
| Net weight | 6.2 kg |
| Gross weight | 6.634 kg |
| Shape of cut-out | round |
| Installation depth | 29.5 cm |
| Installation diameter | 28.5 cm |
| BIG WHITE Page | 837 |