




DASAR 2.0 XL square cover 24° 3000K incl. DALI driver in stainless steel

The DASAR 2.0 accessible recessed floor light has a particularly impressive symmetrical appearance. At the same time, the housing with a round or square cover, as preferred, is made of glass and stainless steel and is both stable and of high quality. The beam angle can be selected between 15°/36° and 60° with interchangeable reflectors. The generously sized mounting pot makes installation both quick and easy. DASAR is a professional lighting experience that can be controlled digitally via DALI.



TECHNICAL DATA

Item no.	1007244
IP Code	IP 65 / IP 67
Impact resistance class	IK 10
Impact resistance	20 Joule
Assembly	Recessed
Assembly details	Ground with Acc.
Dimmable	Yes
Dimming technology	DALI,Touch
Number of through-wires	45
Mechanical loading	2 t
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	19 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	45
Number of luminaires at LS C16A	45
Level of inrush current	10 A
Duration of inrush current	30 µs
Temperature at glass (light emission)	60 °C
Stroboscopic effect (SVM)	0.1

Light Source

1807464	
---------	-----------------------------------------------------------------------------------

Accessories

1007245	Mounting housing for DASAR 2.0
1007239	Reflector for DASAR 2.0 36°
1007238	Reflector for DASAR 2.0 15°
1007240	Reflector for DASAR 2.0 60°

Lumen	1950 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	black
CRI	80
LXXBXX data	L80B50
Service life	50000 h
Risk Group	1
Length	20 cm
Width	20 cm
Depth	18.9 cm
Net weight	3.3 kg
Gross weight	3.531 kg
Shape of cut-out	round
Installation depth	27.4 cm
Installation diameter	28.5 cm
BIG WHITE Page	835